

Fine Pipe-Seal w/ Teflon[®]

Technical Data Sheet

GENERAL INFORMATION: *SAF-T-EZE Fine Pipe-Seal* compound with Teflon* is used where leak resistance is necessary. It can be used on services that contain gasoline, kerosene, LP gases, oil, refrigerants/solvents, mild caustics, many weak acids, water, gas and steam. It can be used on pipes and threaded connections of all materials: iron, stainless steel, aluminum, brass, plastic, etc.

SAF-T-EZE Fine Pipe-Seal is recommended for sealing of joints less than 3/4 inch in diameter. This liquid sealant is self-lubricating in assembly. This product will not swell or attack rubber parts.

Fine Pipe-Seal can be applied just prior to assembly is non-staining and withstands pressures to 10,000 psi. This product can also be pre-applied and allowed to air dry prior to field assembly providing somewhat lower pressure resistance depending upon joint configuration.

PHYSICAL PROPERTIES:

Color	White
Specific Gravity	1.08 g/cc
Performance Temperature	-100°F to +500°F
Flash Point: T.O.C.	55°F

PACKAGING: Available in 4oz Brush Top Cans (FPBT-4), in 8oz Brush Top Cans (FPBT-8), in 16oz Brush Top Cans (FPBT-16), and in 1/2 Gallons Jugs (FP-0.5 Gal).

SHELF LIFE: There is no change in consistency or appearance after one year in a closed container.

CLEAN UP: Alcohol or any petroleum derived solvent, such as paint thinner, naphtha, or petroleum distillate.

NOTE: This product is not recommended for pure oxygen systems.

* DuPont Registered Trademark

IMPORTANT NOTICE: All statements and technical data contained herein are based on tests we believe to be reliable, but the accuracy of completeness thereof is not guaranteed. It is recommended that the buyer test this product to determine its suitability for his application before use. **SAF-T-EZE Div., STL Compound Corporation** is not responsible for loss, claim or damages resulting from use of its products.